

VOLTAS

A TATA Product

VOLTAS



Curved Glass Top Horizontal Freezers

- Curved glass top for better visibility
- Aesthetic soft look design
- Stucco Aluminium inner liner for improved hygiene
- Castor wheels for easy mobility
- UV Grade plastic material for long-lasting appearance
- Environment friendly CFC-free insulation
- Pre-coated body for glossy finish
- Low emissivity glass to avoid cooling loss
- Door lock for restricted accessibility

Technical Specification for Curved Glass Top Horizontal Freezers

S.NO.	Product description	300 L SC/SD (W) CHEST FREEZER GSL	400 L SC/SD (W) CHEST FREEZER GSL
1.	Insulating material	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam
2.	Overall product dimensions (WxDxH) mm	1035 x 690 x 810	1230 x 690 x 810
3.	Packed dimensions (WxDxH) mm	1100 x 770 x 905	1300 x 770 x 905
4.	Storage baskets	Fabricated with wire construction painted epoxy liquid in white	
5.	No. of sliding doors	2	2

Customized Branded Products



As a continuing policy of product innovation at VOLTAS, the above designs and specifications are subject to change without prior notice. The visuals of the product shown above are representative only. Actual product might differ from the one shown above.

Voltas 24x7 Customer Service - 1800 425 4555 (Toll Free) or SMS <AC> to 56677. www.voltasac.com

CORPORATE HEAD OFFICE: Voltas Ltd, A - 43, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi - 110044. Phone: 011 66505550. **BRANCHES:** **DELHI:** Voltas Ltd, A - 43, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi - 110044. Phone: 011-66505550. **HARYANA:** Voltas Ltd, A - 43, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi. Phone: 011-66505582. **GHAZIABAD:** Voltas Ltd, D-15, 3rd Floor, Raj Nagar District Center, Ghaziabad-201001, Phone: 0120-6404801-06. **CHANDIGARH:** Voltas Ltd, SCO NO. 201-203, 2nd Floor Sector 34 A, Chandigarh, Phone: 0172 6610116/17/20. **LUCKNOW:** Voltas Limited, Shalimar Titanium, Block - C, 4th floor, Office Nos. 410 - 412, Plot No. TCG -1/1, Opp. Indira Gandhi Pratishthan, Vibhuti Khand, Gomti Nagar, Lucknow - 226 010, Phone: 0522-6507000. **JAIPUR:** Voltas Ltd, Diamond Tower, 201-203, Purani Chungi, Ajmer Road, Jaipur-302017, Phone: 0141-6451013. **HYDERABAD:** Voltas Ltd, 7-2-1735, Saathinagar, Hyderabad-500018. Phone: 040-66743001. **BANGALORE:** Voltas Ltd, Pride Hulkul, 701, 7th Floor, Lal Bagh road, Opp Passport office, Bengaluru - 560027, Phone: 080-22535600. **CHENNAI:** Voltas Ltd, No. 264, Anna Salai, Chennai - 600018, Phone: 66760333/11. **KOCHI:** Voltas Ltd, Ambanat building, 39/3522, M.G. Road, Ravipuram, Kochi-682016, Phone: 0484-6605555. **COIMBATORE:** Voltas Ltd, 24-2, Pykara Office Road, Tatabad, Coimbatore-6410102, Phone: 0422-6502419/6530080. **MUMBAI:** Voltas Ltd, Voltas House B, 2nd Floor, T.B. Kadam Marg, Chinchpokli, Mumbai - 400033, Phone: 022-66656333. **PUNE:** Voltas Ltd, Equitorial Forum, 2nd & 3rd Floor, Mumbai-Pune Road, Wakadewadi, Pune-411003, Phone: 020-66011776. **THANE:** Voltas Ltd, Unit II, 1st Floor, 2nd Pokhran Road, Thane-400601, Phone: 022-67920106/07. **AHMEDABAD:** Voltas Ltd, A-301, Shivalik Corporate Park, Shivranjini Crossroad Satellite, Ahmedabad-380015, Phone: 0790-66301190/91. **INDORE:** Voltas Ltd, The View, 305, Y.N. Road, 3rd Floor, South Tukoganj Thana, Indore-452001, Phone: 0731-4046393/4043512. **KOLKATA:** Voltas Ltd, Gilanders House, A Block, 4th Floor, 8 N.S. Road, Kolkata-700001, Phone: 033-66266207. For Institutional Inquiry - 09432204056. **PATNA:** Voltas Ltd, Maharaja Complex, 306-A, 3rd Floor, Frazer Road, Patna-800001, Phone: 0612-3222555/6455192. For Institutional Inquiry - 07091091400. **JAMSHEDPUR:** Voltas House, 3rd Floor, Main Road, Bistupur, Jamshedpur - 831001, Phone: 0657-6455921. For Institutional Inquiry - 09771491152. **BHUBANESWAR:** Voltas Ltd, B-15, 2nd Floor, Arihant Plaza, Shaheed Nagar, Bhubaneswar-751007, Phone: 0674 -2544919/18. For Institutional Inquiry -09937140010

Voltas Ltd. adheres to the E-Waste (Management & Handling) Rules 2011 notified by the Ministry of Environment and Forests, Government of India. For more information on Voltas E-Waste and exchange policy please contact 1800-419-3283.

The most trusted way to profit from cooling.





Horizontal Chest Freezers (Metal Top)

- Aesthetic soft look design
- Stucco Aluminium inner liner for improved hygiene
- Castor wheels for easy mobility
- UV Grade plastic material for long-lasting appearance
- Environment friendly CFC-free insulation
- Pre-coated body for glossy finish
- Spring loaded hinges for effortless usage
- Signal indicator for storage protection
- Door lock for restricted accessibility
- Sunken handle for safer operation

Technical Specifications for Metal Top Horizontal Chest Freezers (CFH)

S.NO.	Product description	90 L SD	120 L SD	205 L SD	320 L SD	320 L DD	405 L DD	500 L DD	600 L TD
1.	Insulating material	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam
2.	Overall product dimensions (WxDxH) mm	550 x 565 x 830	670 x 565 x 830	835 x 665 x 830	1180 x 665 x 830	1180 x 665 x 830	1450 x 665 x 830	1680 x 665 x 830	1915 x 665 x 860
3.	Packed dimensions (WxDxH) mm	630 x 620 x 880	730 x 620 x 880	900 x 740 x 880	1240 x 740 x 880	1240 x 740 x 880	1520 x 740 x 880	1740 x 740 x 880	2000 x 770 x 910
4.	No. of baskets	0	0	1	1	1	2	2	2
5.	No. of doors	1	1	1	1	2	2	2	3



Horizontal Chest Freezers (Glass Top)

- Aesthetic soft look design
- Stucco Aluminium inner liner for improved hygiene
- Castor wheels for easy mobility
- UV Grade plastic material for long-lasting appearance
- Environment friendly CFC-free insulation
- Pre-coated body for glossy finish
- Low emissivity glass to avoid cooling loss
- Signal indicator for storage protection
- Door lock for restricted accessibility

Technical Specifications for Glass Top Horizontal Freezers

S.NO.	Product description	205 GSL	320 GSL	405 GSL
1.	Insulating material	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam
2.	Overall product dimensions (WxDxH) mm	848 x 635 x 815	1195 x 635 x 815	1465 x 635 x 815
3.	Packed dimensions (WxDxH) mm	900 x 740 x 880	1240 x 740 x 880	1510 x 740 x 880
4.	Storage baskets	Fabricated with wire construction painted epoxy liquid in white		
5.	No. of sliding doors	2	2	2

Horizontal Chest Cooler (Metal Top)

- Aesthetic soft look design
- High density, high pressure 60mm insulation ensuring minimum heat ingress and low power consumption
- Corrosion resistant with outer body in pre-coated steel sheet
- Tropicalised and energy-efficient R 134a compressor
- Multiple door with sunken handles
- Spring-loaded hinges in doors
- Castor wheels for easy mobility
- Elegant door trims
- Optional accessory
- Customised branding of machines



Technical Specifications for Metal Top Horizontal Chest Coolers (CC)

S.NO.	Product description	90 L SD	120 L SD	205 L SD	320 L SD	320 L DD	405 L DD	500 L DD
1.	Insulating material	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam	60 mm Thick Polyurethane Foam
2.	Overall product dimensions (WxDxH) mm	550 x 565 x 830	670 x 565 x 830	835 x 665 x 830	1180 x 665 x 830	1180 x 665 x 830	1450 x 665 x 830	1680 x 665 x 830
3.	Packed dimensions (WxDxH) mm	630 x 620 x 880	730 x 620 x 880	900 x 740 x 880	1240 x 740 x 880	1240 x 740 x 880	1520 x 740 x 880	1740 x 740 x 880
4.	Gross weight (Kg)	36.5	48	56	70	70	77	91
5.	Net weight (Kg)	30	40	47	60	60	67	79

Visi Cooler

- Aesthetic sleek design
- Castor wheels for easy mobility
- UV Grade plastic materials for long-lasting appearance
- Environment friendly CFC-free insulation
- Powder painted body for glossy finish
- Door lock for restricted accessibility
- Certified performance by international laboratories
- Two pane glass to avoid cooling loss
- Tropicalised compressor

Technical Specifications: Visi Cooler

S.NO.	Product description	70 L SD	120 L SD	220 L SD	320 L SD	425 L SD
1.	No. of doors	1	1	1	1	1
2.	No. of 300 ml bottles	38	65	128	216	316
3.	Overall product dimensions (WxDxH) mm	460 x 535 x 710	480 x 600 x 1040	535 x 580 x 1470	560 x 620 x 1770	650 x 640 x 1975
4.	Packed dimensions (WxDxH) mm	525 x 640 x 775	560 x 635 x 1110	625 x 665 x 1525	650 x 695 x 1825	690 x 715 x 2040

Insulation system 40 mm thick polyurethane foam made up with CFC- free blowing agent.

